## PRODUCT SPECIFICATION

## PS-501T4

## **SPECIFICATIONS**

| Product information |  |
|---------------------|--|
| Air volume          | 1000m³/h                                       |
| Application area    | 200~300m²                                      |
| Shell material      | Metal material                                 |
| Weight              | 31 kg  |
| Product size        | 1205*625*240 mm                                |
| Noise               | ≤50 dB   |
| Filter type         | Primary effciency filter Filter bag (optional) |

| Electrical    |                   |
|---------------|-------------------|
| Rated Voltage | 220V AC / 240V AC |
| Frequency     | 50 / 60 Hz        |
| Power         | 220 W             |

Internal Fuse/overload safety protection design and Power dual protection

| Ionization Tube     |   |
|---------------------|---|
| Quantity            | 4 pcs   |
| Size                | 350 mm  |
| Estimated Tube Life | 17000 Hours   |
| Material            | Various composite materials, stainless steel outer mesh |



## **APPLICATION**

PS-501T4 Apply in hotels, residential, hospitals, nursing, internet cafe, supermarket, restaurants, houses, offce, schools, casinos, public toilets, airports, transportation, underground parking lot, food, animal slaughterhouse, dry goods storage, buildings, warehouses, sewage treatment factories, processing, garbage transfer stations and some commercial and industrial facilities.

Optional accessories: app  $\$  remote control  $\$  ion quantity control system





























